

RMM GEO SERIES/速成 GEO 系列

Gear oil 齿轮油

Product Description/ 产品说明

RMM GEO series are multi-purpose sulfur-phosphorus type hypoid gear lubricant meeting requirement of API Service Classification GL-5. It is manufactured from highest quality base oils fortified with 6 improver, rust inhibitors, foam suppressants, anti-wear and extreme pressure additives and pour point depressants. The multi-viscosity oil formulations permit use over a wide temperature range.

速成 GEO 齿轮油 是高性能的基础油和先进的添加剂配方调制而成的商用车辆齿轮油。这些润滑油专供承受极压和冲击负荷的重负荷车辆的车轴和后桥使用。

Features and Benefits/特征与优越性及优点

- Protects hypoid gears from wear and scuffing.
- Provides rust protection to gear.
- Multi-purpose for minimum inventory.
- Multi-viscosity provides year-round use.
- Non-foaming.
- 卓越的热稳定性和抗高温氧化性
- 卓越的防锈、防腐蚀保护
- 优异的抗磨保护
- 减少磨损，组件寿命较长
- 良好的抗泡沫性能

RMM GEO LSD Limited Slip Drive/速成 GEO LSD 限滑齿轮润滑油

SAE Grade/SAE 黏度等级 80W90

- Excellent Slip Limit performance
- 有效的限滑性能

Applications/应用范围

- Automotive Gearboxes
- General Gear Set
- 手动变速箱
- 后桥

Meet Standard Performance/标准性能达到

- Meets /达到 API GL-5 and MT-1.

Properties and Specifications/典型数据

AWS Series/系列						
SAE Grade /等级		80w90	90	85w140	140	80w90 LSD
Kinematic Viscosity/粘度, @ 40° C, mm2/s, ASTM D445		146	145	358	340	148.4
Kinematic Viscosity/粘度, @ 100° C, mm2/s, ASTM D445		14.7	14.3	25.6	25.1	14.8
Viscosity Index/粘度指数, ASTM D2270		100	96	94	96	100
Density/密度 @ 15°C, g/cm3, ASTM D4052		0.904	0.909	0.908	0.918	0.904
Flash Point/闪点, Cleveland Open Cup, °C, ASTM D92		180	180	215	200	220
Pour Point/倾点, °C, ASTM D97		-30	-18	-15	-9	-30