

Product Description/ 产品说明

RMM Uranium Series are a range of quality premium mineral motor oils designed to provide a high level of performance and protection under most operating conditions.

速成 Uranium 是高性能的汽油发动机系列润滑油，用于帮助保护发动机和保障清洁。速成 Uranium 可在多种工况和应用场合中使用。

Features and Benefits/特征与优越性及优点

- Excellent wear protection
- Excellent engine cleanliness
- High viscosity to reduce leak in high mileage engine
- Excellent high temperature characteristic
- 帮助减少发动机磨损和腐蚀
- 帮助保持发动机清洁
- 良好的高温特性
- 高粘度帮助减少高里程发动机应用中的泄漏

Applications/应用范围

RMM Uranium Series can use for gasoline, diesel and gas engine

速成 Uranium 系列可用于电油，柴油和天然气发动机

Meet Standard Performance/标准性能认可

API SL/CF

Properties and Specifications/典型数据

Uranium Series/系列		
Grade SAE/SAE 粘度等级	15W40	20W50
Ash, Sulfated/硫酸盐灰分, mass%, ASTM D874	0.8	0.8
Density/密度 @ 15° C, g/cm3, ASTM D4052	0.872	0.891
Flash Point/闪点, Cleveland Open Cup, °C, ASTM D92	241	256
Kinematic Viscosity/粘度, @ 100 C, mm2/s, ASTM D445	14.24	17.87
Kinematic Viscosity/粘度, @ 40 C, mm2/s, ASTM D445	106.9	156.33
Pour Point 倾点/, °C, ASTM D97	-27	-33
Viscosity Index/粘度指数, ASTM D2270	135	126